



- Pluggable type 2 AC SPD
- Common & differential mode protection
- I_{max}:40kA@8/20μs
- IEC 61643-11, EN 61643-11



Performance parameters of the product

Model	TM2-40K-1NPE-275V
SPD port	One port
SPD type	T2
Number of poles	1P+N, 230VAC
Network systems	TT, TN-S
Rated voltage U _n	230V AC 50~60Hz
Maximum continuous operating voltage (L-N/N-PE) U _c	275/260 V AC 50~60Hz
Nominal discharge current (8/20 μs) (L-N/N-PE) I _n	20/20kA
Maximum discharge current(8/20 μs) (L-N/N-PE) I _{max}	40/40kA
Protection level (L-N/N-PE) U _p	1.4/1.5kV
Residual current I _{PE}	<1mA
Back-up Fuse(max)	125A gG/gL
Short-circuit Current Rating(AC) I _{SCCR}	25kA
L-TOV 5S (L-N) U _T	335VAC
L-TOV 120min (L-N) U _T	440VAC
H-TOV 200ms (N-PE) U _T	1200VAC
H-TOV 200ms (L-PE) U _T	1450VAC
Response time (L-N/N-PE)	≤25/100ns
Thermal Protection	Yes
Failure indication	Green: normal / Red: failure
Remote alarm	Option TM2-40K-1NPE-440V-S
Installing conductor cross sectional area	4 ~25mm ²
Terminal Screw Torque(max)	4.5N.m
Install	35mm Standard rail (EN50022/DIN46277-3)
Working environment temperature	-40 ~70°C
Enclosure material	Plastic cement, accord with UL94V-0
Enclosure protection level	IP20
Standard	IEC 61643-11, EN 61643-11

Terasaki reserves the right to change, update or correct, without notice, any information contained in this datasheet.

Terasaki Electric Trading & Services(M) Sdn.Bhd.

Address: No.20&22, Jalan Rajawali 2, Bandar Puchong Jaya,
Jalan Puchong, 47100 Puchong, Selangor Darul Ehsan, Malaysia


Website: <https://www.terasaki.com.my>




TemLite Power SPD-TM Range




Dimension drawing



Internal Configuration



Wire-connection diagram



Electrical Symbol



Fuse



MOV



GDT

Terasaki Electric Trading & Services(M) Sdn.Bhd.

Address: No.20&22,Jalan Rajawali 2,Bandar Puchong Jaya,
Jalan Puchong,47100 Puchong,Selangor Darul Ehsan,Malaysia

Website: <https://www.terasaki.com.my>